## Microsoft<sup>®</sup> LifeChat LX-3000





Name Information	
Product Name	Microsoft® LifeChat LX-3000
Headset Name	Microsoft LifeChat LX-3000 Microsoft LifeChat LX-3000
Product Dimensions	WICLOSOFT ETECTIAL EA-3000
	7.04 inches (470 millimators)
Headset Length Headset Width	7.04 inches (178 millimeters)
	6.38 inches (162 millimeters)
Headset Depth/Height	3.11 inches (78.9 millimeters)
Headset Weight	8.32 ounces (236 grams)
Headset Cable Length	72.0 inches +6/-0 inches (1829 millimeters +152/-0 millimeters)
Compatibility and Localization	
Interface	High-speed USB compatible with the USB 2.0 specification
Operating Systems	•Microsoft Windows® 10 / 8.1 / 8 / RT 8.1 / RT 8 / 7, Windows Vista®, and Windows XP with Service Pack 2 (excluding Windows XP 64-bit) • Macintosh MAC OS X v10.7 – 10.11
Top-line System Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems:  • Microsoft Windows 10 / 8.1 / 8 / RT 8.1 / RT 8 / 7, Windows Vista, and Windows XP with Service Pack 2 (excluding Windows XP 64-bit)  • 60 MB hard drive space  • USB port 1.1 (USB 2.0 recommended)
	You must accept License Terms for software download. Please download the latest available software version for your OS/Hardware combination.
	Internet access may be required for certain features. Local and/or long-distance telephone toll charges may apply.
	Software download required for full functionality of all features.
Compatibility Logos	Compatible for Microsoft Windows 10 / 8 / 7     Skype™ for Business Certified
Product Feature Performance	1 Toyler or Table 1
Headset Features	Digital USB
	Built-in unidirectional microphone with acoustic noise cancellation     In-line volume controls     Pivoting boom microphone with 180-degree movement     Windows Live™ Call Button
Windows Live Integration Features	Audio Chat Features: Windows Live Call button delivers one touch access to voice calls and enables automatic audio switching from music to your audic call
Call Button Life	10,000 actuations
Storage Temperature & Humidity	-40 F (-40 °C) to 140 °F (60 °C) with 65% relative humidity (non-condensing)
Operating Temperature & Humidity	32° F (0° C) to 104° F (40° C) with 80% relative humidity (non-condensing)
Certification Information	
Country of Manufacture	People's Republic of China
ISO 9001 Qualified Manufacturer	Yes
ISO 14001 Qualified Manufacturer	Yes
Restriction on Hazardous Substances	This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.
FCC ID	This device complies with Part 15 of the FCC Rules and Industry Canada ICES-003. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC standards. For home and office use. Model number: 1084, LifeChat LX-3000.
Agency and Regulatory Marks	ICES-003 report on file (Canada) EIP Pollution Control Mark, EPUP (China) CE Declaration of Conformity (European Union) WEEE (European Union) VCCI Certificate (Japan) MIC Certificate (Korea) EAC Certificate (Russia) FCC Declaration of Conformity (USA) CB Scheme Certificate (International)
Warranty	2 years
Windows Certification Kit (WCK)	ID: 1751986 (32-bit and 64-bit) Microsoft Windows 10,1608648 (32-bit) and 1608649 (64-bit) Microsoft Windows 8.1

