

MA-303su Portable Wireless PA System

Introduction

MA-303 is a compact, ultra light and robust design wireless PA system. This features-loaded and easy-to-use system can be hand carried, or mounted on a microphone stand and is an excellent public address solution for small to medium crowds.

Ideal applications include: School classrooms & halls, Places of worship, Presentations, seminars and meetings, Day-care activities, playground duty, Indoor/outdoor gatherings, Paging, Shopping center & trade show presentations and promotions, Street performers, Aerobic and fitness centers, Recreational and social activities.

Key Features

- Best-in-class performance.
- Ultra light, ultra compact and ultra portable design.
- Powerful and crystal-clear sound projection.
- Weighs just 2.7 kg (6 pounds)
- One-touch Scan & ACT sync button for fast and easy channel set-up.
- User-friendly control panel provides intuitive easy operation.
- Built-in USB music player & recorder with LCD screen.
- Built-in alarm siren provides emergency warnings.
- High efficiency class-D amplifier drives 2-way speakers with level limiter.
- AC and lithium rechargeable battery operation.
- Up to 11 hours of stand-by time per 4-hour full charge.
- A smart 4-segment battery meter for accurate battery reading and charging status.
- Available in black or white color.

Transmitters & Microphones


ACT-30H	Handheld Transmitter
ACT-30T	Bodypack Transmitter
MM-107	Wired Supercardioid Dynamic Microphone

Accessories

MB-10	Lithium Rechargeable Battery. (14.8V, 2.6AH)
SC-30	Storage and Carry Bag
MS-30	Tripod Microphone Stand
MA-303AXP	Active Extension Speaker
MS-90	Wall-Mounting Bracket

Technical Specifications

Portable PA	
Max. Power Output	60 Watts
Amplifier	Class D
T.H.D.	<1%
Frequency Response	50Hz~18kHz
Speaker	1" Tweeter & 5" Woofer
Coverage	H 120° x V 70°
Audio Inputs	Wired: 6.3mm (1/4") Line-In: 3.5mm (1/8")
Audio Output	3.5mm (1/8")
Alarm Siren	Siren Sound with fade-in mode
Installation	Microphone stand, table mounted.
Power Supply	AC: External 100-240V AC switching power supply DC & Battery: 14.8V/2.6AH rechargeable lithium battery (MB-10x 1)
Charge Time	Up to 4 hours (automatic charging management)
Standby Time	Up to 11 hours
Battery Indicator	4-level indicator (25/50/75/100%)
Color	Black or white option
Dimensions	210(W)× 276(H)× 165(D)mm 8.3(W)× 11(H)× 6.5(D)"
Weight	Approx. 2.7kg 6lbs, battery included
Wireless System	
Receiver Channel	Single
Frequency Range	UHF 480~934 MHz
Bandwidth	24 MHz
Preset Channels	16
Channel Set-up	Scan & ACT sync
Antenna	Built-in
Audio Player	
Built-in USB Port	USB 2.0
USB Play & Record	LCD displays track name, number, time, recording status.



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw

Specifications subject to change without notice. SS015/07

MA-303du Portable Wireless PA System

Introduction

MA-303 is a compact, ultra light and robust design wireless PA system. This features-loaded and easy-to-use system can be hand carried, or mounted on a microphone stand and is an excellent public address solution for small to medium crowds.

Ideal applications include: School classrooms & halls, Places of worship, Presentations, seminars and meetings, Day-care activities, playground duty, Indoor/outdoor gatherings, Paging, Shopping center & trade show presentations and promotions, Street performers, Aerobic and fitness centers, Recreational and social activities.

Key Features

- Best-in-class performance.
- Ultra light, ultra compact and ultra portable design.
- Powerful and crystal-clear sound projection.
- Weighs just 2.8 kg (6.2 pounds)
- One-touch Scan & ACT sync button for fast and easy channel set-up.
- User-friendly control panel provides intuitive easy operation.
- Built-in USB music player & recorder with LCD screen.
- Built-in alarm siren provides emergency warnings.
- High efficiency class-D amplifier drives 2-way speakers with level limiter.
- AC and lithium rechargeable battery operation.
- Up to 9 hours of stand-by time per 4-hour full charge.
- A smart 4-segment battery meter for accurate battery reading and charging status.
- Available in black or white color.

Transmitters & Microphones



ACT-30H	Handheld Transmitter
ACT-30T	Bodypack Transmitter
MM-107	Wired Supercardioid Dynamic Microphone

Accessories

MB-10	Lithium Rechargeable Battery. (14.8V, 2.6AH)
SC-30	Storage and Carry Bag
MS-30	Tripod Microphone Stand
MA-303AXP	Active Extension Speaker
MS-90	Wall-Mounting Bracket

Technical Specifications

Portable PA	
Max. Power Output	60 Watts
Amplifier	Class D
T.H.D.	<1%
Frequency Response	50Hz~18kHz
Speaker	1" Tweeter & 5" Woofer
Coverage	H 120° x V 70°
Audio Inputs	Wired: 6.3mm (1/4") Line-In: 3.5mm (1/8")
Audio Output	3.5mm (1/8")
Alarm Siren	Siren Sound with fade-in mode
Installation	Microphone stand, table mounted.
Power Supply	AC: External 100-240V AC switching power supply DC & Battery: 14.8V/2.6AH rechargeable lithium battery (MB-10 x 1)
Charge Time	Up to 4 hours (automatic charging management)
Standby Time	Up to 9 hours
Battery Indicator	4-level indicator (25/50/75/100%)
Color	Black or white option
Dimensions	210(W)× 276(H)× 165(D)mm 8.3(W)× 11(H)× 6.5(D)"
Weight	Approx. 2.8kg 6.2lbs, battery included
Wireless System	
Receiver Channel	Dual
Frequency Range	UHF 480~934 MHz
Bandwidth	24 MHz
Preset Channels	16
Channel Set-up	Scan & ACT sync
Antenna	Built-in
Audio Player	
Built-in USB Port	USB 2.0
USB Play & Record	LCD displays track name, number, time, recording status.



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw

Specifications subject to change without notice. SS015/07