

# DuraFon PSL-BU

## Long-Range Industrial Cordless Phone System Base Unit

The DuraFon PSL-BU is a single-line base for the DuraFon PRO system. It is an ideal solution when there is a need for an additional line or port to be added to the DuraFon PRO system. The DuraFon PSL base unit provides the same long-range coverage as the DuraFon PRO system to allow users to enjoy having telephone access throughout a large, demanding environment.

As an expansion base for the PRO system the PSL can work behind a standard phone line, or analog ports from a PBX or IP-PBX. As part of the DuraFon PRO system, the DuraFon PSL can be part of an up to eight base unit system and support up to 90 handsets. It also is compatible with the DuraFon PRO, DuraWalkie and DuraFon UHF handsets.

### Users may include:

- Retail Stores°
- Warehouses / Manufacturing facilities
- Hotels / Motels
- Theaters
- Equipment yards



### Key Features

- Digital, long-range cordless base station
- Long-range coverage
- 1-line/port
- Multi-base capacity w/ DuraFon PRO
- 900MHz ISM band
- Optional external indoor / outdoor antenna
- Compatible handsets: DuraFon PRO, DuraWalkie & DuraFon UHF

### Detail Features

- Long range: up to:
  - 12 floors in building penetration (office / motel)
  - 250,000 sq. ft. (warehouse / retail store)
  - 3,000 acres (farm / ranch)
- Frequency band: 902~928MHz
- Single line/port base of DuraFon PRO
- Multi-base (Up to 8 bases)
- Multi-handset (Up to 90 handsets)
- Intercom: Not available from base unit
- Broadcasting: Not available from base unit
- Works on analog CO lines or behind PBX analog ports
- Audio-in jack for music/sales message on hold
- Frequency hopping security: 100 times per second
- Digital spread spectrum (DSS) technology for privacy and clarity
- Optional indoor / outdoor antenna – sold separately
- One year limited warranty
- FCC/IC compliant

## Technical Specifications

### Frequency

902-928 MHz

### RF Power

Peak: 708 mW ; Average:  
304 mW

### Channel Spacing

400 kHz

### Modulation

MSK

### Multiple Access

Frequency Hopping TDMA

### Frequency Hopping Rate

100 per second

### TDMA Frame Length

10 ms

### Number of Slots/Frame

8

### Antenna Gain

2 dBi  
5dBi External (optional)

### TX Power

708mW

### Telephone Interface

RJ11x1

### Speech Coding

8 kbps G.729A

### Channel Coding

8 kbps Convolutional + CRC

### Transmission Data Rate

170.678 kbps

### User Data Rate

128 kbps duplex

### Duplex

Time Division Duplex (TDD)

### Voice Quality

TIA/EIA-470B

### No. of System ID

65,535

### Ring Signal

20-50 Hz, 12-90 Vrms

### Auto-Attendant Coding

8 kbps G.729

### Flash Time

100-900 ms programmable

### Power Source

100~240V/12V AC/DC Adapter

### Charger Current

NA

### Charge Time

NA

### Regulation Compliance

FCC Part 15, Part 68

### Operating Temperature

0~50C

### Storage Temperature

-10~70C

### Humidity

20~75%

### Storage Temperature

-10~70C

### Humidity

20~75%

### Dimension Without Antenna

161W x42D x 188H (mm)

### Weight

424g

## Physical Interface

