

Stain Repellent

Seating

# Punch Card 1242

# Punch Card 1242

Seating

## Specifications

<b>Content</b>	78% polyester 22% post-consumer recycled polyester
<b>Weight</b>	11.1 ± 1.0 oz./lin. yd
<b>Width</b>	54" min. useable
<b>Repeat</b>	25" vertical   12.5" horizontal
<b>Backing</b>	acrylic backcoating
<b>Treatment</b>	stain repellent

## Performance

	<b>Colorfastness to light (AATCC 16.3 Option 3)</b> Grade 4 min. at 40 hours
	<b>Colorfastness to crocking (AATCC 8)</b> Grade 4 min. dry & Grade 3 min. wet
	<b>Breaking Strength (ASTM D5034)</b> 280 lbf warp and 230 lbf fill
	<b>Seam Slippage (ASTM D4034)</b> 105 lbf warp and 60 lbf fill
	<b>Pilling Resistance (ASTM D3511)</b> Class 4
	<b>Flammability</b> CA Technical Bulletin 117-2013 Section 1
	<b>Abrasion (ASTM D4157)</b> 100,000 double rubs cotton duck

\*Certification Marks owned by the Association for Contract Textiles, Inc.

## Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

## Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.

**Proudly woven in North America supporting our local communities.**

## Sustainability



		Alabaster 1301		Putty 1303
	Crimson 1307		Orange 1308	Crisp 1305
Sky 1306		Navy 1309	Burgundy 1311	Peat 1312
Silver Lining 1304		Cadet 1310	Carbon 1302	Abyss 1313

duvaltex

USA & INTERNATIONAL | T 800-544-0200  
CANADA | T 418 227-9897  
For samples, visit [duvaltex.com](http://duvaltex.com)